

Lumievo



V26

PRODUCT CONTENTS

LED BULKHEAD LIGHT

04

DUSAR 300
Polycarbonate



05

DUSAR 275
Die-cast AL



06

DUSAR 350
Die-cast AL



07

DUSAR
SOLAR



08

DUSAR 10
small oval



09

DUSAR 16
large oval



10

DIONE
Square



11

DUSK
Wallpack



13

DROME
Wall Light



LED FLOOD LIGHT

14

NEXUS 100
3CCT&3Watts



15

NEXUS 200
3CCT&3Watts



16

LUMOS
100w-400w



20

LUXOR
50w-400w



26

GAIAZ
500W



27

NEXUS
Solar



WEATHER PROOF LED BATTEN

28

ASTRO
3CCT&2Watts



30

ASTRO
Multi-colors



32

ATLAS
IK10 AL



34

SELOS
IK10 PC



LED DOWNLIGHT

35

SPOTI



36

STELLAR



37

MARS



38

LUMIA



39

LUMIA II



40

ARCHI



LED CEILING LIGHT

42



VIVID

LED STREET LIGHT

45



URANX

50



URANX
Solar

51



Talos

LED CANOPY LIGHT

52



SKYLA

LED Highbay Light

56



Hyx200

57



Hyx300

DESIGNED IN THE USA

00



Cone
Sconce

00



Dome
Lights

00



Ring
Pendant

Installation Hardware

58



Pole Clamp

59



Pole Adaptor

60



Pole Mounting
Clamp Bracket

61



Tri-Bracket

62



Double-Bracket

63



Adjustable
Pole Mount

64



Extension
Arm


65



Flat Mount
Streetlight Brac

Dusar

DSR300



Weather and impact resistant, Selectable colour temperature, LED Bulkhead light Double insulated


A round robust bulkhead light constructed with polycarbonated body and opal diffuser providing decorative solution for both residential and commercial applications.

Microwave and daylight sensor option.

Accessories
Eyelid TRIM



Photometric Diagram



KEY INFORMATION

Lumen Output	1050lm/1680lm
Input Power	12W/16W(Watt-select)
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK/White
Warranty	3 yr
IP Rating	IP65
Ik Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	105 lm/W
LED	SMD
CCT	3000/4000/5000K (CCT-Selectable)
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	220-240V, 50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs

CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Terminal Block
Total Weight	1.6KG
Dimensions	300x95mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Dusar

DSR275
 DSR275-EM
 DSR275-MS
 DSR275-EM-MS



Weather and impact resistant, Selectable colour temperature, LED Bulkhead light


A round robust bulkhead light constructed with aluminum body and opal diffuser providing decorative solution for both residential and commercial applications.

Sensor and Emergency options.

Accessories
 Optional TRIM
 Eyelid/Cross/Grille



Photometric Diagram



KEY INFORMATION

Lumen Output	1050 / 2050 lm
Input Power	10W/20W(Watt-selectable)
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK/White
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	100-110 lm/W
LED	SMD
CCT	3000/4000/5000K (CCT-Selectable)
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	220-240V,50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs

CONSTRUCTION

Housing	Die-cast Aluminum
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Terminal Block
Total Weight	1.3KG
Dimensions	275x80mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Dusar

DSR350
 DSR350-EM
 DSR350-MS
 DSR350-EM-MS



Weather and impact resistant, Selectable colour temperature, LED Bulkhead light


A large round robust bulkhead light constructed with aluminium body and opal diffuser providing decorative solution for both residential and commercial applications.

Sensor and Emergency options.

Accessories
 Optional TRIM
 Eyelid



Photometric Diagram



KEY INFORMATION

Lumen Output	3050 lm
Input Power	30W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK/White
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	100-110 lm/W
LED	SMD
CCT	3000/4000/5000K (CCT-Selectable)
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	220-240V, 50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs

CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Terminal Block
Total Weight	2.6KG
Dimensions	350x110mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Dusar Solar

DSR-SL




Weather and impact resistant, Durable and long lasting,Solar LED Bulkhead light

A round robust bulkhead light constructed with aluminium body and opal diffuser providing decorative solution for both residential and commercial applications. Automatic night-time operation,Smart power battery detection – LED brightness will be automatically reduced to prolong battery life

Accessories
Optional TRIM



Photometric Diagram



KEY INFORMATION

Lumen Output	2400 lm
Input Power	20W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	DIMMABLE
Fitting Colour	BLACK/White
Warranty	3 yr
IP Rating	IP66
Ik Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	120 lm/W
LED	SMD
CCT	6000K
CRI	>80
Beam Angle	120°

ELECTRICAL

Solar panel	15W 6V
Battery	3.7V 12AH,44.4wH
Charging time	~8 Hours (from 0-100%)
Operation time	Dusk to dawn
Sensor	Microwave(up-to10m),180°
Sensor Function	30% standby,100% when motion

CONSTRUCTION


Housing	Aluminium
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Solar panel Dimension	350x350x20mm
Total Weight	2.3KG
Light Dimension	275x80mm
Operating Ambient Temp.	-20 to 45°C
Cable to the solar panel	Aluminium

Warning & Reminding

- This product includes rechargeable batteries which must be adequately charged under sun light before use.
- Before install the light,please press on/off button inside the light to get it activated at the first use.
- The light is equipped with an internal battery pack,which is replaceable.
- Build-in intelligent IC with over-charge,over-discharge,over-temperature protection.
- Please do not dispose the battery with household garbage to avoid explosion.
- Non-professionals please do not disassemble the lamp.

Dusar

DS010




Weather and impact resistant, Selectable colour temperature, LED Bulkhead light

A small oval robust bulkhead light constructed with aluminium body and opal diffuser providing decorative solution for both residential and commercial applications.

Accessories
Optional TRIM



Photometric Diagram



Unit: cd
CO/180 120.0deg
C90/270 120.0deg

KEY INFORMATION

Lumen Output	1050lm
Input Power	10W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK/White
Warranty	5 yr
IP Rating	IP66
IK Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	100-110 lm/W
LED	SMD
CCT	3000/4000/5000K (CCT-Selectable)
CRI	>80
Beam Angle	120°


ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs

CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Terminal Block
Total Weight	1.0 KG
Dimensions	215x135x50mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Dusar

 DSO16
 DSO16-MS


Weather and impact resistant, Selectable colour temperature, LED Bulkhead light


A large oval robust bulkhead light constructed with aluminium body and opal diffuser providing decorative solution for both residential and commercial applications.

Sensor/Photocell Option.

Accessories
 Optional TRIM



Photometric Diagram



KEY INFORMATION

Lumen Output	1650 lm
Input Power	16W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK/White
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	100-110 lm/W
LED	SMD
CCT	3000/4000/5000K (CCT-Selectable)
CRI	>80
Beam Angle	120°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs

CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Terminal Block
Total Weight	1.3 KG
Dimensions	280x185x100mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

DIONE

DIN270
DIN270-EM
DIN270-MS
DIN270-EM-MS


Weather and impact resistant, Selectable colour temperature, LED Bulkhead light

A square robust bulkhead light constructed with aluminium body and opal diffuser providing decorative solution for both residential and commercial applications.

Sensor and Emergency options.



Photometric Diagram



KEY INFORMATION

Lumen Output	1050 / 2050 lm
Input Power	10W/20W(Watt-selectable)
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK/White
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	100-110 lm/W
LED	SMD
CCT	3000/4000/5000K (CCT-Selectable)
CRI	>80
Beam Angle	120°

ELECTRICAL

Driver	Integral
Supply Input	220-240V,50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs

CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Terminal Block
Total Weight	2.0KG
Dimensions	270x270x85mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Dusk

DSK-1628

a robust LED Wallpack constructed with Aluminium body and Polycarbonate opal diffuser providing decorative solution for both residential and commercial applications

*Suitable for use in indoor and outdoor parking areas, tunnels, walkways, building entrances, loading bays, fire assembly points

*Die cast aluminium housing providing optimal heat dissipation and high resistance to weather conditions

*Tritone colour selectable, Multi-watts selectable

*High impact rating of IK06

*High efficacy of 105lm/W

*Wide operating ambient temperature range of -25°C to 40°C

*Suitable for switching by PIR, Microwave or Photocell

*3 hour emergency version available through Conversions



KEY INFORMATION

Lumen Output	1680lm-2940lm
Input Power	16W/20W/24W/28W (Watt-select)
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP65
IK Rating	IK06
IC Rating	N/A

PHOTOMETRIC

Efficacy	105 lm/W
LED	SMD
CCT	3000/4000/5000K (CCT-Selectable)
CRI	>80
Beam Angle	120°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs

CONSTRUCTION

Housing	Die Casting aluminum
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Terminal Block
Total Weight	2.3KG
Dimensions	264x310x118mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Dusk

DSK-3052

a robust LED Wallpack constructed with Aluminium body and Polycarbonate opal diffuser providing decorative solution for both residential and commercial applications

*Suitable for use in indoor and outdoor parking areas, tunnels, walkways, building entrances, loading bays, fire assembly points

*Die cast aluminium housing providing optimal heat dissipation and high resistance to weather conditions

*Tritone colour selectable, Multi-watts selectable

*High impact rating of IK06

*High efficacy of 105lm/W

*Wide operating ambient temperature range of -25°C to 40°C

*Suitable for switching by PIR, Microwave or Photocell

*3 hour emergency version available through Conversions



KEY INFORMATION

Lumen Output	3150lm-5460lm
Input Power	30W/35W/45W/52W (Watt-select)
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP65
Ik Rating	IK06
IC Rating	N/A

PHOTOMETRIC

Efficacy	105 lm/W
LED	SMD
CCT	3000/4000/5000K (CCT-Selectable)
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	220-240V, 50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs

CONSTRUCTION

Housing	Die Casting aluminum
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Terminal Block
Total Weight	2.6KG
Dimensions	270x300x180mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Drome

DRM-70120



The perfect combination of traditional looking design and industry defining selectable features, making it the ideal solution for commercial and residential applications.

*Die cast aluminium housing providing optimal heat dissipation and high resistance to weather conditions

*Tritone colour selectable, Multi-watts selectable

*IP65 waterproof rating

*High efficacy of 105lm/W

*Wide operating ambient temperature range of -25°C to 40°C

*Built-In Photocell

*Five years warranty



KEY INFORMATION

Lumen Output	7350 lm/12600 lm
Input Power	70W/120W (Watt-select)
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	NON-DIMMABLE
Fitting Colour	Dark bronze polyester powder
Warranty	5 yr
IP Rating	IP65
IK Rating	IK06
IC Rating	N/A

PHOTOMETRIC

Efficacy	105 lm/W
LED	SMD
CCT	3000/4000/5000K (CCT-Selectable)
CRI	>80
Beam Angle	120°

ELECTRICAL

Driver	Integral
Supply Input	100-240V,50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs

CONSTRUCTION

Housing	Die Casting aluminum
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Terminal Block
Total Weight	3.0KG
Dimensions	385 x247 x195 mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Nexus

NES100


3-CCT(3K/4K/5K) and
3-Watts (30W/60W/100W)
in one fitting

Ultra-efficient
offset bracket ,
super slim body,
LEDFlood light

Perfect for any exterior space
from residential small
wattage designs through to
high performance commercial
applications



Photometric
Diagram



KEY INFORMATION

Lumen Output	3,000-10,000lm
Input Power	30W/60W/100W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	3 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	100 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	120°

ELECTRICAL

Driver	Integral
Supply Input	200-240V,50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	2.0KG
Dimensions	250 x167 x42 mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Nexus

NES200


3-CCT(3K/4K/5K) and
 3-Watts (120W/150W/200W)
 in one fitting

Ultra-efficient
 offset bracket ,
 super slim body,
 LEDFlood light

Perfect for any exterior space
 from residential small
 wattage designs through to
 high performance commercial
 applications



Photometric
 Diagram



Unit:cd
 C0/180 120.0deg
 C90/270 120.0deg

KEY INFORMATION

Lumen Output	12,000-20,000lm
Input Power	120W/150W/200W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	3 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	100 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	200-240V,50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	3.9 KGS
Dimensions	353 x305 x58 mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Lumos

LUS100



Ultra-efficient offset bracket, super slim body, LEDFlood light


Perfect for any exterior space from residential small wattage designs through to high performance commercial applications

Accessories

Optional Twin Bracket



Photometric Diagram



KEY INFORMATION

Lumen Output	13,000 lm
Input Power	100W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	90°/120°/Asymmetric

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	4.6KG
Dimensions	309x312x53mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Lumos

LUS200




Ultra-efficient offset bracket, super slim body, LED Flood light

Perfect for any exterior space from residential small wattage designs through to high performance commercial applications

Accessories
Optional Twin Bracket



Photometric Diagram



KEY INFORMATION

Lumen Output	26,000 lm
Input Power	200W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	90°/120°/Asymmetric

ELECTRICAL


Driver	Integral
Supply Input	90-305V, 50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	5.7 KG
Dimensions	309x413x53mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Lumos

LUS300





Ultra-efficient offset bracket, super slim body, LEDFlood light

Perfect for any exterior space from residential small wattage designs through to high performance commercial applications

Accessories

Optional Twin Bracket



KEY INFORMATION

Lumen Output	39,000 lm
Input Power	300W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	90°/120°/Asymmetric

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	8.5 KG
Dimensions	411x437x61mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Lumos

LUS400




Ultra-efficient offset bracket, super slim body, LEDFlood light


Perfect for any exterior space from residential small wattage designs through to high performance commercial applications

Accessories

Optional Twin Bracket



CO/180 90.0deg C90/270 90.0deg



Asymmetric CO/180 124.2deg C90/270 36.9deg

KEY INFORMATION

Lumen Output	52,000 lm
Input Power	400W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	90°/120°/Asymmetric

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	11.0 KG
Dimensions	515x443x62mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Luxor

LXR50




Ultra-efficient offset bracket, super slim body, LEDFlood light

Perfect for any exterior space from residential small wattage designs through to high performance commercial applications

Accessories
Optional Twin Bracket



Photometric Diagram



KEY INFORMATION

Lumen Output	6500 lm
Input Power	50W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	90°/120°/Asymmetric

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	3.0KG
Dimensions	288.3x228.0x51.8mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Luxor

LXR100




Ultra-efficient offset bracket, super slim body, LEDFlood light

Perfect for any exterior space from residential small wattage designs through to high performance commercial applications

Accessories
Optional Twin Bracket



Photometric Diagram



KEY INFORMATION

Lumen Output	13,000 lm
Input Power	100W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	90°/120°/Asymmetric

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	5.2KG
Dimensions	364.3x278.0x51.8mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Luxor

LXR150




Ultra-efficient offset bracket, super slim body, LEDFlood light

Perfect for any exterior space from residential small wattage designs through to high performance commercial applications

Accessories
Optional Twin Bracket



Photometric Diagram



KEY INFORMATION

Lumen Output	19,500 lm
Input Power	150W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	90°/120°/Asymmetric

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	6.6KG
Dimensions	394.5x393.5x56.6mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Luxor

LXR200



Ultra-efficient offset bracket, super slim body, LEDFlood light

Perfect for any exterior space from residential small wattage designs through to high performance commercial applications

Accessories
Optional Twin Bracket



Photometric Diagram

KEY INFORMATION

Lumen Output	26,000 lm
Input Power	200W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	90°/120°/Asymmetric

ELECTRICAL

Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	7.3 KG
Dimensions	445.5x392.5x56.8mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Luxor

LXR300




Ultra-efficient offset bracket, super slim body, LEDFlood light


Perfect for any exterior space from residential small wattage designs through to high performance commercial applications

Accessories

Optional Twin Bracket



CO/180 90.0deg C90/270 90.0deg



Asymmetric

CO/180 123.4deg C90/270 36.5deg

KEY INFORMATION

Lumen Output	39,000 lm
Input Power	300W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	90°/120°/Asymmetric

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	11.5 KG
Dimensions	523.5x545.6x64.8mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Luxor

LXR400




Ultra-efficient offset bracket, super slim body, LEDFlood light

Perfect for any exterior space from residential small wattage designs through to high performance commercial applications

Accessories

Optional Twin Bracket



KEY INFORMATION

Lumen Output	52,000 lm
Input Power	400W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	90°/120°/Asymmetric

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	12.0 KG
Dimensions	523.5x545.6x64.8mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Gaiax

Gax500



Symmetrical or asymmetrical, Robust Gaiax LED Flood light


Ideal for harsh conditions, with superior housing made of LM6 grade die-cast aluminium, in addition to a chromated and powder-coated black finish

Accessories


Optional Hood/Twin Bracket



Photometric Diagram Unit: cd



CO/180 60.0deg C90/270 60.0deg



Asymmetric

CO/180 124.6deg C90/270 49.3deg

KEY INFORMATION

Lumen Output	70,000 lm
Input Power	500W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
IK Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	140 lm/W
LED	SMD
CCT	3000/4000/5000K
CRI	>80
Beam Angle	60°/Asymmetric


ELECTRICAL

Driver	Integral
Supply Input	90-305V, 50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	12.0 KG
Dimensions	531x128x377mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Nexus Solar




Ultra-efficient offset bracket, super slim body, LEDFlood light

Perfect for any exterior space from residential small wattage designs through to high performance commercial applications



Photometric Diagram



Unit: cd
 C0/180 120.0deg
 C90/270 120.0deg

KEY INFORMATION

Sensor	Microwave sensor
Detect Distance	8m
Sensor function	30% standby, 100% motion 30 seconds
Winter Eco Mode	50% Brightness Dusk to Dawn
Remote	IR
Fitting Colour	BLACK
Warranty	3 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Lumen Output	4,000lm
LED	SMD
CCT	6000K
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	/
Supply Input	Solar Powered
Power Factor	/
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	Yes

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	180°
Battery	3.2V 30Ah,96WH
Solar Panel	5V / 40W, 670 x 443 x 22 mm
Total Weight	3.9 KGS
Dimensions	320x388 x50 mm
Separate solar panel with 5 m cable	

Astro

Asr600




The ability to select your preferred lumen output/wattage within one light fitting.

These are the perfect option when simple functionality is required. Rear and side entry options for easy linking and conduit entry. Combined diffuser and gear tray lead to exceptionally fast fit off. Vandal resistant latches can be secured to stop any tampering. 3 Colour selection with a fixed power driver.



Photometric Diagram



KEY INFORMATION

Lumen Output	13,00 lm/26,00 lm
Input Power	10W/20W (Watt-select)
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	Grey base
Warranty	5 yr
IP Rating	IP65
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-Select)
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	180mins(Emergency Option)
Sensor	Setting via Remote(Sensor Option)

CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	0.82 KG
Dimensions	600x95x80mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Astro

Asr1200




The ability to select your preferred lumen output/wattage within one light fitting.

These are the perfect option when simple functionality is required. Rear and side entry options for easy linking and conduit entry. Combined diffuser and gear tray lead to exceptionally fast fit off. Vandal resistant latches can be secured to stop any tampering. 3 Colour selection with a fixed power driver.



Photometric Diagram



KEY INFORMATION

Lumen Output	26,00 lm/52,00 lm
Input Power	20W/40W (Watt-select)
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	Grey base
Warranty	5 yr
IP Rating	IP65
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-Select)
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	180mins(Emergency Option)
Sensor	Setting via Remote(Sensor Option)

CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	1.28 KG
Dimensions	1200x95x80mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Astro

B/G/R/A600



Dual colour selections
 Blue or Green, Red or
 Amber Wavelength / CCT


—
 Blue: 450 – 470 nm,
 Green: 510 – 530 nm,
 Amber: 1800 K,
 Red: 615 – 635 nm

These are the perfect option when simple functionality is required. Rear and side entry options for easy linking and conduit entry. Combined diffuser and gear tray lead to exceptionally fast fit off.

Vandal resistant latches can be secured to stop any tampering.



Photometric Diagram



KEY INFORMATION

Dual colour	Blue+Green OR Red+Amber
Dual Wattage	10W/20W (Watt-select)
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	Grey base
Warranty	5 yr
IP Rating	IP65
Ik Rating	IK08/IK10
IC Rating	N/A

PHOTOMETRIC

Blue	450-470nm
Green	510-530nm
Amber	1800K
Red	615-635nm
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	200-240V, 50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	180mins(Emergency Option)
Sensor	Setting via Remote(Sensor Option)

CONSTRUCTION

Housing	Polycarbonate/Diecasting Aluminium
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	0.82 KG
Dimensions	600x95x80mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Astro

B/G/R/A1200



Dual colour selections

Blue or Green, Red or Amber

Wavelength / CCT –

Blue: 450 – 470 nm,


Green: 510 – 530 nm,

Amber: 1800 K,

Red: 615 – 635 nm

These are the perfect option when simple functionality is required. Rear and side entry options for easy linking and conduit entry. Combined diffuser and gear tray lead to exceptionally fast fit off.

Vandal resistant latches can be secured to stop any tampering. Robust polycarbonate/diecasting aluminum body and UV-stabilized polycarbonate diffuser.



KEY INFORMATION

Dual colour	Blue+Green OR Red+Amber
Dual Wattage	20W/40W (Watt-select)
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	Grey base
Warranty	5 yr
IP Rating	IP65
Ik Rating	IK08/IK10
IC Rating	N/A

PHOTOMETRIC

Blue	450-470nm
Green	510-530nm
Amber	1800K
Red	615-635nm
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	200-240V, 50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	180mins(Emergency Option)
Sensor	Setting via Remote(Sensor Option)

CONSTRUCTION

Housing	Polycarbonate/Diecasting Aluminum
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	1.28 KG
Dimensions	1200x95x80mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Atlas

Ats600




a Strong IK10 robust weatherproof batten, built for tough conditions.

The control gear has been designed to be simplified, ultra-efficient and versatile with Lumen Select Technology, 1 luminaire with multiple wattages/lumen outputs in the same traditional body and diffuser making it easier to replace keeping the same appearance through your installation.



4-Watts Select
3-CCT Select



KEY INFORMATION

Lumen Output	3,640-5,200lm
Input Power	28/32/36/40W (Watt-select)
Hole Cutout Size	N/A
Install	Surface mount
Dimming Options	NON-DIMMABLE/DALI/0-10V Dimming
Fitting Colour	Grey base
Warranty	5 yr
IP Rating	IP65
Ik Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-Select)
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	180mins(Emergency Option)
Sensor	Setting via Remote(Sensor Option)

CONSTRUCTION

Housing	Diecast Aluminum
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	2.1 KG
Dimensions	660x110x95mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Atlas

Ats1200




a Strong IK10 robust weatherproof batten, built for tough conditions.

The control gear has been designed to be simplified, ultra-efficient and versatile with Lumen Select Technology, 1 luminaire with multiple wattages/lumen outputs in the same traditional body and diffuser making it easier to replace keeping the same appearance through your installation.



Photometric Diagram



4-Watts Select
3-CCT Select

KEY INFORMATION

Lumen Output	6,240-7,800lm
Input Power	48/52/56/60W (Watt-select)
Hole Cutout Size	N/A
Install	Surface mount
Dimming Options	NON-DIMMABLE/DALI/0-10V Dimming
Fitting Colour	Grey base
Warranty	5 yr
IP Rating	IP65
Ik Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-Select)
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	180mins(Emergency Option)
Sensor	Setting via Remote(Sensor Option)

CONSTRUCTION

Housing	Diecast Aluminium
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	3.3 KG
Dimensions	1170x110x95mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Selos

Sel600




The ability to select your preferred lumen output/wattage within one light fitting.

These are the perfect option when simple functionality is required. Rear and side entry options for easy linking and conduit entry. Combined diffuser and gear tray lead to exceptionally fast fit off. Vandal resistant latches can be secured to stop any tampering. 3 Colour selection with a fixed power driver.



Photometric Diagram



KEY INFORMATION

Lumen Output	1,100-2,200 lm
Input Power	10W/20W (Watt-select)
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	Grey base
Warranty	3 yr
IP Rating	IP65
IK Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	110 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-Select)
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	200-240V, 50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	180mins(Emergency Option)
Sensor	Setting via Remote(Sensor Option)

CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	2.00 KG
Dimensions	675x96x116mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Spoti

Spt90




SPOTI multi-function
fixed or gimble 60
degree beam reflector
style downlight.

A low maintenance solution
that is ideal for residential
apartments, foyers, retail,
restaurants and clubs
where an energy efficient
and reliable lamp
performance is essential.

Optional
Triac/DALI/0-10V Dimming



CCT-Select



KEY INFORMATION

Lumen Output	720 lm
Input Power	9W
Hole Cutout Size	90mm
Install	Recessed
Dimming Options	Triac/DALI/0-10V DIMMABLE
Fitting Colour	WHITE
Warranty	5 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	IC-4

PHOTOMETRIC

Efficacy	80 lm/W
LED	COB
CCT	3000/4000/5000K(CCT-select)
CRI	>90
Beam Angle	45°/60°

ELECTRICAL


Driver	External
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Diecasting Aluminium
Optics	Optics Lens
Adjustable Angle	60°
Fixings/Hardware	N/A
Connection Type	N/A
Total Weight	370 g
Dimensions	φ108xH36mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class II

Stellar

Stl90



STELLAR multi-function fixed or gimble 60 degree beam reflector style downlight.


A low maintenance solution that is ideal for residential apartments, foyers, retail, restaurants and clubs where an energy efficient and reliable lamp performance is essential.

Optional
Triac/DALI/0-10V Dimming



CCT-Select

Photometric Diagram



KEY INFORMATION

Lumen Output	720 lm
Input Power	9W
Hole Cutout Size	90mm
Install	Recessed
Dimming Options	Triac/DALI/0-10V DIMMABLE
Fitting Colour	WHITE
Warranty	5 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	IC-4

PHOTOMETRIC

Efficacy	80 lm/W
LED	COB
CCT	3000/4000/5000K(CCT-select)
CRI	>90
Beam Angle	45°/60°

ELECTRICAL


Driver	External
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Diecasting Aluminium
Optics	Optics Lens
Adjustable Angle	60°
Fixings/Hardware	N/A
Connection Type	N/A
Total Weight	360 g
Dimensions	φ108xH36mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class II

Mars

Mas70



MARS is a multi-function fixed fire rated led downlight.


A low maintenance solution that is ideal for residential apartments, foyers, retail, restaurants and clubs where an energy efficient and reliable lamp performance is essential.

Optional
Triac/DALI/0-10V Dimming



CCT-Select

Photometric Diagram



KEY INFORMATION

Lumen Output	560 lm
Input Power	7W
Hole Cutout Size	70mm
Install	Recessed
Dimming Options	Triac/DALI/0-10V DIMMABLE
Fitting Colour	WHITE
Warranty	5 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	IC-4

PHOTOMETRIC

Efficacy	80 lm/W
LED	COB
CCT	2700/3000/4000K(CCT-select)
CRI	>90
Beam Angle	60°

ELECTRICAL

Driver	Internal
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Diecasting Aluminium
Optics	Optics Lens
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	N/A
Total Weight	220 g
Dimensions	φ83xH85mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class II

Lumia


Lum70
Lum90
Lum110
Lum140
Lum150
Lum200

Tritone colour selection allows easy adjustment of colour temperature.

Tritone selectable
Built-in dimmable driver
(1-100%)
IC-4 rating (ta 25°C)
Recessed diffuser
IP44 from below



Photometric Diagram



CCT-Select

KEY INFORMATION

Lumen Output	595-2200 lm
Input Power	7w/10w/13w/16w/20w/22w
Hole Cutout Size	70/90/110/140/150/200 mm
Install	Recessed
Dimming Options	Triac DIMMABLE
Fitting Colour	WHITE
Warranty	3 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	IC-4

PHOTOMETRIC

Efficacy	95 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	110°

ELECTRICAL

Driver	Internal
Supply Input	200-240V,50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	N/A
Total Weight	N/A
Dimensions	φ92/φ115/φ140/φ170/φ190/φ235mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class II

Lumia II


LumII90

10w Low Glare
 Reflector Down Light
 with Tritone
 switchable colour
 temperature

Tritone selectable
 Built-in dimmable driver
 (1-100%)
 IC-4 rating (ta 25°C)
 Recessed diffuser
 IP44
 60° Beam angle



CCT-Select

 Photometric
 Diagram

 Unit: cd
 CO/180 60.0deg
 C90/270 60.0deg

KEY INFORMATION

Lumen Output	900 lm
Input Power	10W
Hole Cutout Size	90mm
Install	Recessed
Dimming Options	Triac DIMMABLE
Fitting Colour	WHITE
Warranty	3 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	IC-4

PHOTOMETRIC

Efficacy	90 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	60 °

ELECTRICAL

Driver	Internal
Supply Input	200-240V,50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A


CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	N/A
Total Weight	250 g
Dimensions	φ108xH90 mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class II

ARCHI

ARC165

ARCHI multi-function
fixed style downlight.




A low maintenance solution that is ideal for residential apartments, foyers, retail, restaurants and clubs where an energy efficient and reliable lamp performance is essential.

Optional

Triac/DALI/0-10V Dimming



Photometric Diagram



CCT-Select

KEY INFORMATION

Lumen Output	2000 lm
Input Power	20W
Hole Cutout Size	16mm
Install	Recessed
Dimming Options	Triac/DALI/0-10V DIMMABLE
Fitting Colour	WHITE
Warranty	5 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	IC-4

PHOTOMETRIC

Efficacy	100 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	100°

ELECTRICAL

Driver	External
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Diecasting Aluminum
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	N/A
Total Weight	900 g
Dimensions	φ190xH45mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class II

ARCHI

ARC200

ARCHI multi-function
fixed style downlight.




A low maintenance solution that is ideal for residential apartments, foyers, retail, restaurants and clubs where an energy efficient and reliable lamp performance is essential.

Optional

Triac/DALI/0-10V Dimming



Photometric Diagram



Unit: cd
CO/180 99.6deg
C90/270 100.2deg

CCT-Select

KEY INFORMATION

Lumen Output	2500 lm
Input Power	25W
Hole Cutout Size	200mm
Install	Recessed
Dimming Options	Triac/DALI/0-10V DIMMABLE
Fitting Colour	WHITE
Warranty	5 yr
IP Rating	IP44
IK Rating	N/A
IC Rating	IC-4

PHOTOMETRIC

Efficacy	100 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	100°

ELECTRICAL


Driver	External
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Diecasting Aluminium
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	N/A
Total Weight	1200 g
Dimensions	φ228xH45mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class II

Vivid

Vid250




A slimline quick installation ceiling light with improved efficacy and output.

Vivid comes with quick fit mounting bracket, integral control gear and offers discrete appearance for residential, commercial and retail applications. Colour temperature can be set at 3000K, 4000K or 5000K with switch located on the back of the fitting.

Optional:
DALI/0-10V Dimming



Photometric Diagram



CCT-Select

KEY INFORMATION

Lumen Output	1,440 lm
Input Power	12W
Hole Cutout Size	N/A
Install	Surface Mount
Dimming Options	NON-DIMMABLE/DALI/0-10V DIMMABLE
Fitting Colour	WHITE
Warranty	5 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	N/A

PHOTOMETRIC

Efficacy	120 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	Microwave(Sensor optional)

CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting plate
Connection Type	N/A
Total Weight	450 g
Dimensions	φ250xH60mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Vivid

Vid300



A slimline quick installation ceiling light with improved efficacy and output.


Vivid comes with quick fit mounting bracket, integral control gear and offers discrete appearance for residential, commercial and retail applications. Colour temperature can be set at 3000K, 4000K or 5000K with switch located on the back of the fitting.

Optional:
DALI/0-10V Dimming



CCT-Select

Photometric Diagram



KEY INFORMATION

Lumen Output	2,160 lm
Input Power	18W
Hole Cutout Size	N/A
Install	Surface Mount
Dimming Options	NON-DIMMABLE/DALI/0-10V DIMMABLE
Fitting Colour	WHITE
Warranty	5 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	N/A

PHOTOMETRIC

Efficacy	120 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	Microwave(Sensor optional)

CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting plate
Connection Type	N/A
Total Weight	850 g
Dimensions	φ300xH60mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Vivid

Vid380



A slimline quick installation ceiling light with improved efficacy and output.


Vivid comes with quick fit mounting bracket, integral control gear and offers discrete appearance for residential, commercial and retail applications. Colour temperature can be set at 3000K, 4000K or 5000K with switch located on the back of the fitting.

Optional:
DALI/0-10V Dimming



CCT-Select

Photometric Diagram



KEY INFORMATION

Lumen Output	2,880 lm
Input Power	24W
Hole Cutout Size	N/A
Install	Surface Mount
Dimming Options	NON-DIMMABLE/DALI/0-10V DIMMABLE
Fitting Colour	WHITE
Warranty	5 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	N/A

PHOTOMETRIC

Efficacy	120 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Integral
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	Microwave(Sensor optional)

CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting plate
Connection Type	N/A
Total Weight	1.4 KG
Dimensions	φ380xH60mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Uranx

Urx3060



A slimline performance street lantern with improved efficacy and output.

Uranx offers a choice of optics with asymmetrical distribution including an area optic.


Optional Accessories

Shorting Cap/PE Cell
DALI/0-10V Dimming



Watt-Select
CCT-Select

Photometric Diagram



KEY INFORMATION

Lumen Output	4,500 lm/7800lm
Input Power	30W/60W(Watt-select)
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE/DALI/0-10V DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130-150 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	80°x150°

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	PE CELL Available

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	90°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	4.8 KG
Dimensions	568x200x109mm(No shorting cap)
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Uranx

Urx100



A slimline performance street lantern with improved efficacy and output.

Uranx offers a choice of optics with asymmetrical distribution including an area optic.


Optional Accessories

Shorting Cap/PE Cell
DALI/0-10V Dimming



CCT-Select

Photometric Diagram



KEY INFORMATION

Lumen Output	13,000 lm
Input Power	100W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE/DALI/0-10V DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	80°x150°

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	PE CELL Available

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	90°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	5.2 KG
Dimensions	613x240x109mm(No shorting cap)
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Uranx

Urx150



A slimline performance street lantern with improved efficacy and output.


Uranx offers a choice of optics with asymmetrical distribution including an area optic.

Optional Accessories

Shorting Cap/PE Cell
DALI/0-10V Dimming



CCT-Select



KEY INFORMATION

Lumen Output	19,500 lm
Input Power	150W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE/DALI/0-10V DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	80°x150°

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	PE CELL Available

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	90°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	6.1 KG
Dimensions	683x260x109mm(No shorting cap)
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Uranx

Urx200



A slimline performance street lantern with improved efficacy and output.

Uranx offers a choice of optics with asymmetrical distribution including an area optic.


Optional Accessories

Shorting Cap/PE Cell
DALI/0-10V Dimming



CCT-Select

Photometric Diagram



KEY INFORMATION

Lumen Output	26,000 lm
Input Power	200W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE/DALI/0-10V DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	80°x150°

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	PE CELL Available

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	90°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	6.7 KG
Dimensions	693x300x109mm(No shorting cap)
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Uranx

Urx300



A slimline performance street lantern with improved efficacy and output.

Uranx offers a choice of optics with asymmetrical distribution including an area optic.


Optional Accessories

Shorting Cap/PE Cell
DALI/0-10V Dimming



CCT-Select

Photometric Diagram



Unit: cd
CO/180 148.1deg
C90/270 77.1deg

KEY INFORMATION

Lumen Output	39,000 lm
Input Power	300W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE/DALI/0-10V DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK08
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	80°x150°

ELECTRICAL


Driver	Integral
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	PE CELL Available

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	90°
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	7.9 KG
Dimensions	793x300x109mm(No shorting cap)
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Uranx Solar

Urx-sl



Carefully matched packages of solar panel (with Battery), Light head (with Controller) and Cabling.

Plug-and-play pairing of light head and solar panel unit. Quality componentry matched for reliability of output as a top priority

Optional Accessories
Spigot 60mm/76mm/89mm

KEY INFORMATION

Plug & Play connectivity

Rating: IP66


Impact Rating: IK10 (Light head), IK08 (Solar Panel)

304 stainless steel screws included


Accessories: Bird spikes included

Spigot Options: Ø60mm/Ø76mm/Ø89mm

- Pre-program: Auto-ON at dusk. Auto-OFF at dawn
- Built-in infra-red motion sensor regulates light output automatically.
- Changes from dim mode (30%) to bright mode (100%) upon motion detection.
- Working time: ≥10hrs bright mode. ≥30 hrs dim mode.



Photometric Diagram



Single Head Solar Streetlight Kit:

Model : Urx-SL-S

Power:15W

3CCT : 3000K/4000K/5000K Selectable

Optics: T2M Lens

Solar panel: 424*403*24mm

Solar module: 30W, 18VDC

Composition: Monocrystalline Silicon PV

Battery: Lithium Iron Phosphate LiFePO4, 12Ah / 144Wh

Weight: Panel 7.1kg. Light head 4.5kg



Double Head Solar Streetlight Kit:

Model : Urx-SL-T

Power: 15w+15w

3CCT : 3000K/4000K/5000K Selectable

Optics: T2M Lens

Solar panel: 803*424*24mm

Solar module: (30W, 18VDC) x2

Composition: Monocrystalline Silicon PV


Battery: Lithium Iron Phosphate LiFePO4, 12Ah / 144Wh x2

Weight: Light head 4.5kg x2, Panel 14.8kg



Talos

Tls60




A slimline performance

LED Post Top Lantern
with improved efficacy
and
output.

Talos offers a choice of optics with asymmetrical distribution including an area optic.



Photometric Diagram



KEY INFORMATION

Lumen Output	6,000 lm
Input Power	60W(Dimmable)
Hole Cutout Size	N/A
Install	N/A
Dimming Options	DIMMABLE Via Remote
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP66
Spigot	IK08 76mm or 60mm

PHOTOMETRIC

Efficiency	100lm/w
LED	SMD
CCT	3000K-5000K Dimmable Via Remote
CRI	80
Beam Angle	70°x150°/150°x80°/50°x140°/140°x140°

ELECTRICAL


Driver	Integral
Supply Input	220-240V,50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	Optional

CONSTRUCTION

Housing	Aluminium
Optics	Tempered Glass
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	5.8 KG
Dimensions	Ø452 x H542 mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Skyla

Sky100-L



An industrial-grade commercial fixture for ceiling and canopy lighting.


The uniquely designed housing ensures optimum thermal management for the integrated LED module. SKYLA series is easy to install onto a variety of ceiling surfaces and can be used for any industrial or commercial project. Typical applications include carparks, petrol stations, warehouses etc.

Optional Accessories

Installation plate



Photometric Diagram



KEY INFORMATION

Lumen Output	13,000 lm
Input Power	100W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	White
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	130 lm/W
LED	SMD
CCT	5000K
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Meanwell
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	11.3KG
Dimensions	580x580x125mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Skyla

Sky100-S



An industrial-grade commercial fixture for ceiling and canopy lighting.


The uniquely designed housing ensures optimum thermal management for the integrated LED module. SKYLA series is easy to install onto a variety of ceiling surfaces and can be used for any industrial or commercial project. Typical applications include carparks, petrol stations, warehouses etc.

Optional Accessories

Installation plate



Photometric Diagram



KEY INFORMATION

Lumen Output	10,000 lm
Input Power	100W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	White
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	100 lm/W
LED	SMD
CCT	5000K
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Meanwell
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	6.7KG
Dimensions	455x455x110mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Skyla

Sky150-L



An industrial-grade commercial fixture for ceiling and canopy lighting.


The uniquely designed housing ensures optimum thermal management for the integrated LED module. SKYLA series is easy to install onto a variety of ceiling surfaces and can be used for any industrial or commercial project. Typical applications include carparks, petrol stations, warehouses etc.

Optional Accessories

Installation plate



Photometric Diagram



KEY INFORMATION

Lumen Output	18,000 lm
Input Power	150W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	White
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	120 lm/W
LED	SMD
CCT	5000K
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Meanwell
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	11.3KG
Dimensions	580x580x125mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Skyla

Sky200-L



An industrial-grade commercial fixture for ceiling and canopy lighting.


The uniquely designed housing ensures optimum thermal management for the integrated LED module. SKYLA series is easy to install onto a variety of ceiling surfaces and can be used for any industrial or commercial project. Typical applications include carparks, petrol stations, warehouses etc.

Optional Accessories

Installation plate



Photometric Diagram



KEY INFORMATION

Lumen Output	24,000 lm
Input Power	200W
Hole Cutout Size	N/A
Install	N/A
Dimming Options	NON-DIMMABLE
Fitting Colour	White
Warranty	5 yr
IP Rating	IP66
Ik Rating	IK10
IC Rating	N/A

PHOTOMETRIC

Efficacy	120 lm/W
LED	SMD
CCT	5000K
CRI	>80
Beam Angle	120°

ELECTRICAL


Driver	Meanwell
Supply Input	90-305V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	N/A
Total Weight	11.3KG
Dimensions	580x580x125mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Hymnx

Hyx200




The Hymnx Highbay is 3 power switchable and tritone selectable. Offering precision optics for improved performance and a tough aluminium housing with optimised heat dissipation, to ensure prolonged LED life.

Option:
Plug-in 15m PIR Sensor



Photometric Diagram



KEY INFORMATION

Lumen Output	16,000 - 33,000 lm
Watt-select	100w-150w-200w
Hole Cutout Size	N/A
Install	N/A
Dimming Options	0-10V Dimmable
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP65
IK Rating	IK08
Optional lens	Anti-Glare Lens

PHOTOMETRIC

Efficiency	160lm/w
LED	SMD
CCT	3000K-4000K-5000K Switchable
CRI	80
Beam Angle	120°

ELECTRICAL


Driver	SOSEN
Supply Input	90-305V AC 50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	15m PIR sensor

CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Suspension
Total Weight	4.8 KG
Dimensions	Ø310x H150 mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

Hymnx

Hyx300




The Hymnx Highbay is 3 power switchable and tritone selectable. Offering precision optics for improved performance and a tough aluminium housing with optimised heat dissipation, to ensure prolonged LED life.

Option:
 Plug-in 15m PIR Sensor



Photometric Diagram



KEY INFORMATION

Lumen Output	33,800 - 51000 lm
Watt-select	200w-250w-320w
Hole Cutout Size	N/A
Install	N/A
Dimming Options	0-10V Dimmable
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP65
IK Rating	IK08
Optional lens	Anti-Glare Lens

PHOTOMETRIC

Efficiency	160lm/w
LED	SMD
CCT	3000K-4000K-5000K Switchable
CRI	80
Beam Angle	90°

ELECTRICAL

Driver	SOSEN
Supply Input	90-305V AC 50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	15m PIR sensor



CONSTRUCTION

Housing	Aluminium
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Suspension
Total Weight	6.8 KG
Dimensions	Ø360x H200 mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1

60-90mm Pole Clamp

Our outdoor mounting hardware is made from Galvanized Steel and Anti-salt spray powder to prevent oxidation and suit our harsh environment.

Design with grip teeth for extra stability to prevent mast shifting
Heavy-duty construction



Pole Adaptor




Our outdoor mounting hardware is made from Galvanized Steel and Anti-salt spray powder to prevent oxidation and suit our harsh environment.

Our customized Pole Adaptor is a convenient solution for reducing the spigot size of a pole or outreach arm.

Finish
Hot Dip Galvanised

Available in custom sizes to suit the specific needs of your project.

For example:
 $\varnothing 80\text{mm} > \varnothing 60\text{mm}$



Pole Mounting Clamp Bracket

Material

Mild Steel

Finish

Anti-Corrosive AkzoNobel

Powder Coat

Ingress Protection

IP66

Impact Rating

IK10

Max. Top Weight

8.7kg



Tri-Bracket Floodlight Pole Mast

Material

Mild Steel

Finish

Anti-Corrosive AkzoNobel

Powder Coat

Ingress Protection

IP66

Impact Rating

IK10

Spigot Size

60mm/76mm/89mm, or
any customization size

Max. Top Weight

26.1kg

Application

Steel Light Poles



Dual Mount Floodlight Bracket



Material

Mild Steel

Finish

Anti-Corrosive AkzoNobel

Powder Coat

Ingress Protection

IP66

Impact Rating

IK10

Dimensions

220mm (H) x 250mm (L)

Spigot Size

60mm / 76mm

Max. Top Weight

17.4kg

Application

Steel Light Poles



Adjustable Pole Mount



Material

Premium Grade

Aluminium

Finish

Anti-Corrosive AkzoNobel

Powder Coat

Ingress Protection

IP68

Impact Rating

IK10

Spigot Size

60mm

Max. Top Weight

8.7kg

Floodlight Mount Arm

Use a Floodlight Mount Arm bracket to mount floodlights on walls for signage.

Material

Mild Steel Arm

Finish

Anti-Corrosive AkzoNobel

Powder Coat

Dimensions

500mm/ 800mm/

1000mm

Ingress Protection



IP66

Impact Rating

IK10

Application

Signage



Flat Mount Streetlight Bracket

Streetlight Brackets are exceptional in terms of strength. This Streetlight Mounting bracket is used for positioning streetlights on buildings and is resistant to extreme weather conditions.

Being stylish in appearance and easy to install, it is widely demanded by our clients. We can customize it for any diameter Spigots.

Material Specifications

Material

Mild Steel

Finish

Hot Dip Galvanised
(Optional Black Powdercoat)

Mounting


Pole Mounted at 15° Tilt

Warranty

5 Year Replacement

Benefits

Can be Painted, or Powdercoated



Explores Possibilities

Shenzhen Lumievo Technology Co.,Ltd
Building B2, 2nd Ming Jin Hai Industrial Park, Shiyan, Ban An
District, Shenzhen 518108
Tel: 0086 139 2655 6020
Email: sales@lumievo.com