


ARCHI

ARC200

ARCHI multi-function fixed style downlight.



A low maintenance solution that is Ideal for residential apartments, foyers, retail, restaurants and clubs where an energy efficient and reliable lamp performance is essential.


Optional

Triac/DALI/0-10V Dimming



CCT-Select

Photometric Diagram



Unit: cd
CO/180 99.6deg
C90/270 100.2deg

KEY INFORMATION

Lumen Output	2500 lm
Input Power	25W
Hole Cutout Size	200mm
Install	Recessed
Dimming Options	Triac/DALI/0-10V DIMMABLE
Fitting Colour	WHITE
Warranty	5 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	IC-4

PHOTOMETRIC

Efficacy	100 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	100°

ELECTRICAL

Driver	External
Supply Input	200-240V,50/60Hz
Power Factor	>0.95
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Diecasting Alumnium
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	N/A
Total Weight	1200 g
Dimensions	φ228xH45mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class II