

# DIONE Emergency

DIN270-EM


Weather and impact resistant, Selectable colour temperature, LED Bulkhead light

A square robust bulkhead light constructed with aluminium body and opal diffuser providing decorative solution for both residential and commercial applications.

Accessories  
Optional TRIM



Photometric Diagram



Unit: cd  
 CO/180 120.0deg  
 C90/270 120.0deg

## KEY INFORMATION

Lumen Output	1050 / 2050 lm
Input Power	10W/20W(Watt-selectable)
Hole Cutout Size	N/A
Install	<b>SURFACE MOUNT</b>
Dimming Options	<b>NON-DIMMABLE</b>
Fitting Colour	<b>BLACK/White</b>
Warranty	5 yr
IP Rating	<b>IP66</b>
Ik Rating	<b>IK10</b>
IC Rating	N/A

## PHOTOMETRIC

Efficacy	100-110 lm/W
LED	<b>SMD</b>
CCT	<b>3000/4000/5000K (CCT-Selectable)</b>
CRI	<b>&gt;80</b>
Beam Angle	<b>120°</b>

## ELECTRICAL

Driver	<b>Integral</b>
Supply Input	<b>220-240V,50/60Hz</b>
Power Factor	<b>&gt;0.9</b>
Useful life @Ta 25°(L70)	<b>50,000hrs</b>
Emergency time	<b>3hr</b>

## CONSTRUCTION

Housing	<b>Aluminium</b>
Optics	<b>Polycarbonate Diffuser</b>
Adjustable Angle	<b>N/A</b>
Fixings/Hardware	<b>Mounting Screws</b>
Connection Type	<b>Terminal Block</b>
Total Weight	<b>2.0KG</b>
Dimensions	<b>270x270x85mm</b>
Operating Ambient Temp.	<b>-20 to 45°C</b>
Electrical Classification	<b>Class 1</b>