

Dusk

DSK-3052

a robust LED Wallpack constructed with Aluminium body and Polycarbonate opal diffuser providing decorative solution for both residential and commercial applications

*Suitable for use in indoor and outdoor parking areas, tunnels, walkways, building entrances, loading bays, fire assembly points

*Die cast aluminium housing providing optimal heat dissipation and high resistance to weather conditions

*Tritone colour selectable, Multi-watts selectable

*High impact rating of IK06

*High efficacy of 105lm/W

*Wide operating ambient temperature range of -25°C to 40°C

*Suitable for switching by PIR, Microwave or Photocell

*3 hour emergency version available through Conversions



KEY INFORMATION

Lumen Output	3150lm-5460lm
Input Power	30W/35W/45W/52W (Watt-select)
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	NON-DIMMABLE
Fitting Colour	BLACK
Warranty	5 yr
IP Rating	IP65
Ik Rating	IK06
IC Rating	N/A

PHOTOMETRIC

Efficacy	105 lm/W
LED	SMD
CCT	3000/4000/5000K (CCT-Selectable)
CRI	>80
Beam Angle	120°

ELECTRICAL

Driver	Integral
Supply Input	220-240V,50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs

CONSTRUCTION

Housing	Die Casting aluminum
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Terminal Block
Total Weight	2.6KG
Dimensions	270x300x180mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1