

Lumia

Lum70


Tritone colour selection allows easy adjustment of colour temperature.

Tritone selectable
 Built-in dimmable driver (1-100%)
 IC-4 rating (ta 25°C)
 Recessed diffuser
 IP44 from below



CCT-Select

Photometric Diagram



Unit: cd
 CO/180 111.0deg
 C90/270 111.5deg

KEY INFORMATION

Lumen Output	630 lm
Input Power	7W
Hole Cutout Size	70mm
Install	Recessed
Dimming Options	Triac DIMMABLE
Fitting Colour	WHITE
Warranty	3 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	IC-4

PHOTOMETRIC

Efficacy	90 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	110°

ELECTRICAL

Driver	Internal
Supply Input	200-240V,50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	N/A
Total Weight	220 g
Dimensions	φ97xH55mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class II