

# Lumia

Lum90


Tritone colour selection allows easy adjustment of colour temperature.

Tritone selectable  
 Built-in dimmable driver (1-100%)  
 IC-4 rating (ta 25°C)  
 Recessed diffuser  
 IP44 from below



CCT-Select

Photometric Diagram



Unit: cd  
 CO/180 111.0deg  
 C90/270 111.5deg

## KEY INFORMATION

Lumen Output	855 lm
Input Power	9W
Hole Cutout Size	90mm
Install	Recessed
Dimming Options	Triac DIMMABLE
Fitting Colour	WHITE
Warranty	3 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	IC-4

## PHOTOMETRIC

Efficacy	95 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	110°

## ELECTRICAL

Driver	Internal
Supply Input	200-240V,50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

## CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	N/A
Total Weight	250 g
Dimensions	φ115xH58mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class II