

# Lumia II

LumII90


10w Low Glare  
Reflector Down Light  
with Tritone  
switchable colour  
temperature

Tritone selectable  
Built-in dimmable driver  
(1-100%)  
IC-4 rating (ta 25°C)  
Recessed diffuser  
IP44  
60° Beam angle



CCT-Select

Photometric Diagram



Unit: cd  
 CO/180 60.0deg  
 C90/270 60.0deg

## KEY INFORMATION

Lumen Output	900 lm
Input Power	10W
Hole Cutout Size	90mm
Install	Recessed
Dimming Options	Triac DIMMABLE
Fitting Colour	WHITE
Warranty	3 yr
IP Rating	IP44
Ik Rating	N/A
IC Rating	IC-4

## PHOTOMETRIC

Efficacy	90 lm/W
LED	SMD
CCT	3000/4000/5000K(CCT-select)
CRI	>80
Beam Angle	60 °

## ELECTRICAL

Driver	Internal
Supply Input	200-240V,50/60Hz
Power Factor	>0.9
Useful life @Ta 25°(L70)	50,000hrs
Emergency time	N/A
Sensor	N/A

## CONSTRUCTION

Housing	Polycarbonate
Optics	Polycarbonate
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	N/A
Total Weight	250 g
Dimensions	φ108xH90 mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class II